

DS-7732NI-Q4 NVR

Key Feature

- Up to 32-ch IP camera inputs
- H.265+/H.265/H.264+/H.264 video formats
- Up to 1-ch@8 MP or 6-ch@1080p decoding capacity
- Up to 160 Mbps incoming bandwidth
- 4 HDDs for continuous video recording



Professional and Reliability

- H.265+ compression effectively reduces the storage space by up to 75%
- Adopt stream over TLS encryption technology which provides more secure stream transmission service

HD Video Output

- Provide simultaneous HDMI and VGA outputs
- HDMI video output at up to 4K resolution

Storage and Playback

- 4 SATA interfaces for HDD connection (up to 8 TB capacity per HDD)
- 16-ch synchronous playback

Smart Function

- Support multiple VCA (Video Content Analytics) events
- Configurable special camera smart functions, such as VCA detection (motion, line crossing, intrusion, etc.)

Network & Ethernet Access


- 2 self-adaptive 10/100/1000 Mbps Ethernet interfaces
- Hik-Connect & DDNS (Dynamic Domain Name System) for easy network management



▪ Specification


Video and Audio	
IP Video Input	32-ch Up to 8 MP resolution
Incoming Bandwidth	160 Mbps
Outgoing Bandwidth	80 Mbps
HDMI Output	1-ch, 4K (4096 x 2160)/30 Hz, 4K (3840 x 2160)/30 Hz, 2K (2560 x 1440)/60 Hz, 1920 x 1080/60 Hz, 1600 x 1200/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz
VGA Output	1-ch, 1920 x 1080/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz
Video Output Mode	HDMI/VGA simultaneous output
Audio Output	1-ch, RCA (Linear, 1 k Ω)
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 k Ω)
Decoding	
Decoding Format	H.265/H.265+/H.264/H.264+
Decoding Capability	1-ch@8 MP (30 fps)/6-ch@1080p (30 fps) *: The length or width of camera resolution (each track) cannot exceed 4096 pixels.
Synchronous playback	16-ch
Recording Resolution	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF
Stream Type	Video, Video & Audio
Audio Compression	G.711ulaw/G.711alaw/G.726
Network	
Remote Connection	64
Network Protocol	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS
Network Interface	2, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Auxiliary Interface	
SATA	4, SATA interface
Capacity	Up to 8 TB capacity for each disk
Serial Interface	1 RS-485 (half-duplex), 1 RS-232
USB Interface	Front panel: 2 x USB 2.0; Rear panel: 1 x USB 2.0
Alarm In/Out	16/4
General	
Power Supply	100 to 240 VAC, 50 to 60 Hz
Consumption	≤ 15 W (without HDD)
Working Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working Humidity	10 % to 90 %
Dimension (W x D x H)	440 x 397 x 75 mm (17.3" x 15.6" x 3.0")
Weight	≤ 5 kg (without HDD, 11 lb.)
Certification	
FCC	Part 15 Subpart B, ANSI C63.4-2014
CE	EN 55032: 2015, EN 61000-3-2, EN 61000-3-3, EN 50130-4, EN 55035: 2017

Dimension



scale/1:1;Unit/mm

Physical Interface



No.	Description	No.	Description
1	LAN Network Interface	7	USB Interface
2	AUDIO OUT	8	Alarm In; Alarm Out; RS-485 Serial Interface
3	AUDIO IN	9	GND
4	HDMI Interface	10	100 to 240 VAC Power Supply
5	VGA Interface	11	Power Switch
6	RS-232 Serial Interface		

Available Model

DS-7732NI-Q4

Distributed by



Headquarters

No.565 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-800-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28499800
sales@pram@hikvision.com

Hikvision Canada
T +1-866-200-8660
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9940
sales.thailand@hikvision.com

Hikvision Europe
T +31-20-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0458-6002
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
latam.support@hikvision.com

Hikvision Turkey
T +90 (216) 521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-0413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01525-502140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (12) 0351170
sales.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-050
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730067
nails.panfilov@hikvision.ru

Hikvision Vietnam
T +84-074270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4452080
sales.ae@hikvision.com

Hikvision Singapore
T +65-6804-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-67-1238-8430
uzb@hikvision.tu

Hikvision Hong Kong
T +852-2351-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-880-87-89
sales.ru@hikvision.com

Hikvision Korea
T +82-1031-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com