

## DS-7716NI-Q4/16P NVR

### Key Feature

- Up to 16-ch IP camera inputs
- H.265+/H.265/H.264+/H.264 video formats
- Up to 1-ch@8 MP or 6-ch@1080p decoding capacity
- Up to 160 Mbps incoming bandwidth
- 4 HDDs for continuous video recording



### Professional and Reliability

- H.265+ compression effectively reduces the storage space by up to 75%
- Adopt stream over TLS encryption technology which provides more secure stream transmission service

### HD Video Output

- Provide simultaneous HDMI and VGA outputs
- HDMI video output at up to 4K resolution

### Storage and Playback

- 4 SATA interfaces for HDD connection (up to 8 TB capacity per HDD)
- 16-ch synchronous playback

### Smart Function

- Support multiple VCA (Video Content Analytics) events
- Configurable special camera smart functions, such as VCA detection (motion, line crossing, intrusion, etc.)

### Network & Ethernet Access

- 16 independent PoE network interfaces
- 1 self-adaptive 10/100/1000 Mbps Ethernet interface
- Hik-Connect & DDNS (Dynamic Domain Name System) for easy network management




## ▪ Specification

Video and Audio	
IP Video Input	16-ch Up to 8 MP resolution
Incoming Bandwidth	160 Mbps
Outgoing Bandwidth	80 Mbps
HDMI Output	1-ch, 4K (4096 x 2160)/30 Hz, 4K (3840 x 2160)/30 Hz, 2K (2560 x 1440)/60 Hz, 1920 x 1080/60 Hz, 1600 x 1200/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz
VGA Output	1-ch, 1920 x 1080/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz
Video Output Mode	HDMI/VGA simultaneous output
Audio Output	1-ch, RCA (Linear, 1 k $\Omega$ )
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 k $\Omega$ )
Decoding	
Decoding Format	H.265/H.265+/H.264/H.264+
Decoding Capability	1-ch@8 MP (30 fps)/6-ch@1080p (30 fps) *: The length or width of camera resolution (each track) cannot exceed 4096 pixels.
Synchronous playback	16-ch
Recording Resolution	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF
Stream Type	Video, Video & Audio
Audio Compression	G.711ulaw/G.711alaw/G.726
Network	
Remote Connection	64
Network Protocol	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS
Network Interface	1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
PoE	
Interface	16, RJ-45 10/100 Mbps self-adaptive Ethernet interface
Power	≤ 150 W
Supported standard	IEEE 802.3 af/at
Auxiliary Interface	
SATA	4, SATA interface
Capacity	Up to 8 TB capacity for each disk
Serial Interface	1 RS-485 (half-duplex), 1 RS-232
USB Interface	Front panel: 2 x USB 2.0; Rear panel: 1 x USB 2.0
Alarm In/Out	16/4
General	
Power Supply	100 to 240 VAC, 50 to 60 Hz
Consumption	≤ 15 W (without HDD and PoE off)
Working Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working Humidity	10 % to 90 %
Dimension (W x D x H)	445 x 400 x 75 mm (17.5" x 15.7" x 3.0")
Weight	≤ 5 kg (without HDD, 11 lb.)

**Certification**


FCC	Part 15 Subpart B, ANSI C63.4-2014
CE	EN 55032: 2015, EN 61000-3-2, EN 61000-3-3, EN 50130-4, EN 55035: 2017

**Dimension**



scale/1:1;Unit/mm

## Physical Interface



No.	Description	No.	Description
1	PoE Interface	7	VGA Interface
2	USB Interface	8	RS-232 Serial Interface
3	LAN Network Interface	9	Alarm In; Alarm Out; RS-485 Serial Interface
4	AUDIO OUT	10	GND
5	AUDIO IN	11	100 to 240 VAC Power Supply
6	HDMI Interface	12	Power Switch

## Available Model

DS-7716NI-Q4/16P

Distributed by



### Headquarters

No.565 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseas@hikvision.com

**Hikvision USA**  
T +1-800-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4213  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28498800  
sales@pram@hikvision.com

**Hikvision Canada**  
T +1-866-200-8690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9940  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0458-6002  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216) 521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-0413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01525-802140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (12) 0351170  
sales.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-050  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-8730067  
nails.pantlov@hikvision.ru

**Hikvision Vietnam**  
T +84-074270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4452080  
sales.ae@hikvision.com

**Hikvision Singapore**  
T +65-6804-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-67-1238-8430  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2351-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-880-87-88  
sales.ru@hikvision.com

**Hikvision Korea**  
T +82-0631-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com