NVR





8MP/6MP/5MP/4MP/3MP/1080P/720P HD NVR



TD-3116B1





HD IPC



























4K Output

Audio

MIC

Mobile

USB

Mouse

TD-3116B1 supports 16 CH 8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/ 960P/720P high definition IP video input, which adopts the most advanced SOC technique to ensure high definition recording in each channel and realize outstanding robustness of the system.

TD-3116B1 supports 16 CH IP input, simultaneous 16 CH playback, and 4K ultra-high definition display. The series of product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.









en tyt net en For more information, please visit our website


Specifications

| | Model | TD-3116B1 |
|------------------|-----------------------------|---|
| System | OS | Embedded Linux |
| Video | Network Input | 16 CH IPC input |
| | Network Input Resolution | 8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/ 960H/D1/CIF |
| | Output | $HDMI \times 1: 3840 \times 2160 / 1920 \times 1080 / 1280 \times 1024 / 1024 \times 768 \\ VGA: 1920 \times 1080 / 1280 \times 1024 / 1024 \times 768$ |
| | Compression | H.265S / H.265+ / H.265 / H.264 |
| Audio | Network Input | 16 CH IPC audio input |
| | 2-way Audio | RCA×1 |
| | Local Output | RCA×1 |
| | Compression | G.711(U/A) |
| Live View | Decoding Capability | 1CH 8MP; 4CH 1080P |
| Record | Record Stream | Dual stream recording |
| | Resolution | 8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/ 960H/D1/CIF |
| | Frame Rate | N:30fps; P:25fps |
| Playback | Simultaneous Playback | Max. 16 CH |
| | Search | Time slice / time / event / tag / smart search |
| | Smart Search | Highlighted color to display the camera record in a certain period of time, different colors refers to different record events |
| | Function | Play, pause, FF, FB, digital zoom, etc. |
| Alarm | Mode | Manual, sensor, motion, exception, smart events |
| | Input | Supports IPC alarm input |
| | Output | Supports IPC alarm output |
| | Triggering | Record, snap, preset, e-mail, etc. |
| Network | Interface | RJ 45 1000Mbps × 1 |
| | Protocol | TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP, HTTP, HTTPs, 802.1x, ONVIF, etc. |
| | Incoming Bandwidth | 112Mbps |
| | Outgoing Bandwidth | 112Mbps |
| | Client Connection | Max. 10 users access |
| Mobile Device | os | iOS, Andriod |
| Storage | HDD Interface | SATA 3.0 × 1, max 8T |
| Backup | Local Backup | U disk, USB mobile HDD |
| | Network Backup | Yes |
| Port | USB | USB 2.0 × 2 |
| | Remote Controller | Optional |
| Others | Power Supply | DC 12V/1.5A |
| | Consumption | ≤ 10W (without HDD) |
| | Dimensions (mm) | 300 × 249 × 45 (W × D × H) |
| | Working Environment | -10 ~ 50°C, 10% ~ 90% humidity |
| | Certificate | CE, FCC |
| | Environmental Protection | Complies with Directive EU RoHS, REACH and WEEE |

Features

- Supports 16CH 8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/ 960H/DI/CIF IP video input
- H.265S / H.265+ / H.265 / H.264 coding
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: manual / timed / motion / sensor / POS / AI recording
- Playback: 16CH simultaneous playback
- Search: time slice, time, event, tag and smart search
- Supports multiple VCA (Video Content Analytics) events, such as object abandoned/missing, region intrusion, tripwire, video exception, etc.
- Supports POS information overlay on live view and playback
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via Web or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log view and device status view
- 4K output, true high resolution display
- Supports NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Andriod OS

DIMENSIONS





TD-3116B1

Rear Panel

TD-3116 B1

