


CAMERA

TD-9583E3L

8MP HD AI Dome Network Camera



- Smart H.265/H.264 coding
- Max.resolution: 8MP (3840 × 2160)
- ICR auto switch, true day / night vision
- 3D DNR, true WDR, HLC, BLC and ROI coding
- 30~50m IR night view distance; Motorized zoom lens
- 1CH audio input; 1CH audio output; 1CH built-in MIC
- 1CH alarm input; 1CH alarm output; 1CH CVBS video output
- Built-in micro SD card slot, up to 256GB
- DC12V/PoE power supply
- Support three streams
- P2P function optional
- IP 67&IK10
- Support mobile surveillance by smart phones with iOS and Android OS
- Intelligent analytics



en.tvt.net.cn

For more information, please visit our website

Shenzhen TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 23rd Floor, Block B4, Building NO.9, Shenzhen Bay Eco-Technology Park, Nanshan District, Shenzhen, Guangdong Province, P.R.China

Tel: +86-755-36995888

Web site: <http://en.tvt.net.cn>

Fax: +86-755-33104777


E-mail: overseas@tvt.net.cn

SPECIFICATIONS

Specifications	Model	TD-9583E3L
Camera		
Image Sensor		1 / 2.8" CMOS
Image Size		3840×2160
Electronic Shutter		1 / 25 s ~ 1 / 100000 s
Iris Type		DC Iris
Min. Illumination		0.01 lux @ F1.2, AGC ON; 0 lux with IR 0.015 lux@F1.4, AGC ON; 0 lux with IR
Lens		2.8~12mm@F1.4, motorized
Field of View		Horizontal: 96°~32°; Vertical:64°~18.4°; Diagonal: 103.8°~36.5°
Lens Mount		Φ14
Day&Night		ICR
Wide Dynamic Range		120dB
BLC		Yes
HLC		Yes
Defog		Yes
Digital NR		3D DNR
Angle Adjustment		Pan: 0°~345°; Tilt:0°~77°; Rotation: 0°~345°
Image		
Video Compression		Smart H.265 / H.265+ / H.265 / Smart H.264 / H.264+ / H.264 / MJPEG
H.264 Compression Standard		Baseline Profile/Main Profile/High Profile
Resolution		8MP (3840 × 2160), 6MP(3072 × 2048),5MP(2592 × 1944), 4MP(2592 × 1520), 2K (2560 × 1440), 3MP (2304 × 1296), 1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480 × 240
Main Stream		60Hz : 8MP/6MP(1~20fps), 5MP/4MP/2K/3MP/1080P/720P(1~30fps) 50Hz : 8MP/6MP(1~20fps), 5MP/4MP/2K/3MP/1080P/720P(1~25fps) HFR Mode: 1080P/720P(60Hz: 1~60fps; 50Hz: 1~50fps)
Sub Stream		720P/D1/CIF/480 × 240 (60Hz: 1~30fps; 50Hz: 1~25fps)
Third Stream		D1/CIF/480 × 240 (60Hz: 1~30fps; 50Hz: 1~25fps)
Bit Rate		64 Kbps ~ 12 Mbps
Bit Rate Type		VBR / CBR
Audio Compression		G711A / U
Image Settings		ROI, Saturation, Brightness, Chroma, Contrast,Wide Dynamic, Sharpen, NR,etc. adjustable through client software or web browser
ROI		Each ROI to be configured separately
Intelligent Analytics (Smart Events)		
Perimeter Protection		Line crossing, region entrance/exiting/intrusion (human/motor vehicle/ non-motor vehicle classification)
Target Counting		Line crossing human/motor vehicle/non-motor vehicle counting
Exception Detection		Scene change, video blur and video color cast detection
Face Detection		Face detection and face capture
General Intelligence		Crowd density detection, heat map, object abandoned/missing detection*
Interfaces		
Network		RJ45
Video Output		CVBS output (BNC×1)
Audio		1CH audio input; 1CH audio output; 1CH built-in MIC
Storage		Built-in micro SD card slot; up to 256GB
Reset		Yes
Alarm		1CH alarm input; 1CH alarm output
Functions		
Remote Monitoring		Web browsing, CMS remote control
Online Connection		Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol		UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, UPnP, HTTPs, QoS
Interface Protocol		ONVIF
Storage		Network remote storage; micro SD card storage
Smart Alarm		Motion detection; sensor alarm, SD card error; SD card full, IP address conflict, cable disconnection

General Function	Watermark, IP address filtering, video mask, heartbeat, password protection, image distortion correction, etc.
IR Distance	30~50m
Protection Grade	IP 67&IK10
PoE	Yes (IEEE802.3af)
Others	
Power Supply	DC12V/PoE
Power Consumption	< 10.5W
Operating Environment	- 30 °C ~ 60 °C (-22°F~140°F) Humidity: less than 95 % (non-condensing)
Dimensions (mm)	Φ 141 × 100.2
Weight (net)	Approx. 0.89KG
Installation	Ceiling mounting; Wall mounting
Certificate	CE, FCC
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)

DIMENSIONS



AVAILABLE ACCESSORIES



AVAILABLE MODEL

Available Model	TD-9583E3L(D/AZ/PE/AR3)	Motorized zoom lens
-----------------	-------------------------	---------------------

*Grey items are being developed and coming soon.