


CAMERA

# TD-9442E3H

## 4MP IR Water-Proof Bullet Network Camera



- H.265+ / H.265 / H.264+ / H.264 / MJPEG
- Max. resolution: 2560 × 1440
- Starlight
- ICR auto switch, true day / night vision
- 30~50m IR night view distance
- 3D DNR, true WDR, HLC, BLC, Defog, NIR, Smart IR and ROI coding
- Support image distortion correction
- Built-in micro SD card slot; up to 256GB
- DC12V/PoE power supply
- IP 67 ingress protection
- Support three streams
- P2P function optional
- Support remote monitoring by smart phones & tablet PCs with iOS and Android OS
- Intelligent analytics



en.tvt.net.cn

For more information, please visit our website

**Shenzhen TVT DIGITAL TECHNOLOGY CO., LTD.**

Address: 23<sup>rd</sup> Floor, Block B4, Building NO.9, Shenzhen Bay Eco-Technology Park, Nanshan District, Shenzhen, Guangdong Province, P.R.China

Tel: +86-755-36995888

Web site: <http://en.tvt.net.cn>

Fax: +86-755-33104777


E-mail: [overseas@tvt.net.cn](mailto:overseas@tvt.net.cn)

### SPECIFICATIONS

Specifications	Model	TD-9442E3H
<b>Camera</b>		
Image Sensor		1 / 1.8" CMOS
Image Size		2576 × 1452
Electronic Shutter		1 s ~ 1 / 100000 s
Iris Type		Fixed Iris
Min. Illumination		0.0009lux@F1.2,AGC ON; 0 lux with IR 0.0016 lux@F1.6,AGC ON; 0 lux with IR
Lens		2.8 mm@F1.65, H.FoV: 111.3°; V.FoV:78.9°; D.FoV:118.4° 3.6 mm@F1.6, H.FoV: 88.4°; V.FoV: 57.8°; D.FoV:96.3°
Focus		Fixed
Lens Mount		M12
Day & Night		ICR
Wide Dynamic Range		120dB
BLC		Yes
HLC		Yes
Defog		Yes
Digital NR		3D DNR
Angle Adjustment		Pan: 0°~360°; Tilt:0°~90°; Rotation: 0°~360°
<b>Image</b>		
Video Compression		Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG
H.264 Compression Standard		Baseline Profile/Main Profile/High Profile
Resolution		4MP(2560×1440), 3MP(2304×1296), 1080P (1920×1080), 720P (1280×720), D1, CIF, 480×240
Main Stream		4MP/3MP/1080P / 720P( 60Hz : 1 ~ 30fps; 50Hz: 1~25fps ) HFR mode: 1080P / 720P( 60Hz : 1 ~ 60fps; 50Hz: 1~50fps )
Sub Stream		720P/D1/CIF( 60Hz : 1 ~ 30fps; 50Hz: 1~25fps )
Third Stream		D1/CIF/480×240 ( 60Hz : 1 ~ 30fps; 50Hz: 1~25fps )
Bit Rate		64 Kbps ~ 8 Mbps
Bit Rate Type		VBR / CBR
Audio Compression		G711A / U
Image Settings		ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, NR, etc. adjustable through client software or web browser
ROI		Each ROI to be configured separately
<b>Interfaces</b>		
Network		RJ 45
Video Output		No
Audio		1 CH audio input
Storage		Built-in micro SD card slot; up to 256GB
Reset		Yes
Alarm		No
<b>Intelligent Analytics (Smart Events)</b>		
Perimeter Protection		Line crossing, intrusion (human/motor vehicle/non-motor vehicle classification)
Target Counting		Line crossing human/motor vehicle/non-motor vehicle counting
Exception Detection		Scene change, video blur and video color cast detection
Face Detection		Face detection and face capture
<b>Functions</b>		
Remote Monitoring		Web browsing, CMS remote control
Online Connection		Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol		UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, ICMP, IGMP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, 802.1x, UPnP, HHTPs, QoS
Interface Protocol		ONVIF
Storage		Network remote storage; micro SD card storage
Smart Alarm		Motion detection, SD card error, SD card full

General Function	Watermark, IP address filtering, video mask, heartbeat, password protection, image distortion correction, non-photosensitive switch
PoE	Yes, IEEE802.3af
IR Distance	30 ~ 50 m
Ingress Protection	IP 67
<b>Others</b>	
Power Supply	DC12V/PoE
Power Consumption	< 7.5W
Operating Environment	- 30 °C ~ 60 °C (-22°F~140°F) Humidity: less than 95 % (non-condensing)
Dimensions ( mm )	217.8 × 80.5 × 80.3
Weight ( net )	Approx. 0.68KG
Installation	Ceiling mounting; Wall mounting
Certificate	CE, FCC
Environmental Protection	Directive EU RoHS, WEEE(2012/19/EU), directive 94/62/EC and REACH(EC1907/2006)

### DIMENSIONS



### AVAILABLE ACCESSORIES



### AVAILABLE MODEL

Available Model	TD-9442E3H(D/PE/AR3)	Fixed lens
-----------------	----------------------	------------