

## DS-3E0518P-E/M 16-Port Gigabit Unmanaged PoE Switch

DS-3E0518P-E/M switch is a layer 2 PoE network switch, providing 16 × Gigabit PoE ports and 2 × Gigabit SFP fiber optical ports. On top of high-performance access, the switch provides advanced PoE power technology to guarantee the stable network upload of the adaptive data.



### Feature and Function

- 16 × Gigabit PoE ports, 2 × Gigabit SFP fiber optical ports.
- IEEE 802.3at/af standard.
- IEEE 802.3, IEEE 802.3u, and IEEE 802.3x standard.
- 6 KV surge protection for PoE ports.
- PoE power management.
- Gigabit network access.
- Wire-speed forwarding
- Store-and-forward switching.
- Solid high-strength metal shell.




## Specification

Model		DS-3E0518P-E/M
Network parameters	Port number	16 × Gigabit PoE ports, 2 × Gigabit SFP fiber optical ports
	Port type	RJ45 port, full duplex, MDI/MDI-X adaptive
	Standard	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
	Forwarding mode	Store-and-forward switching
	MAC address table	8 K
	Switching capacity	36 Gbps
	Packet forwarding rate	26.784 Mpps
	Internal cache	4.1 Mbits
PoE power supply	PoE standard	IEEE 802.3af, IEEE 802.3at
	PoE power pin	Ethernet cable 1/2/3/6 provide power supply.
	PoE port	Ports 1 to 16
	Max. port power	30 W
	PoE power budget	125 W
	Max. power consumption	150 W
General	Shell	Metal material, no fan equipped.
	Net weight	2.500 kg (5.51 lb)
	Gross weight	3.570 kg (7.87 lb)
	Dimension (L × H × D)	440 mm × 44 mm × 220.8 mm (17.3" × 1.7" × 8.7")
	Operating temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Storage temperature	-40 °C to 85 °C (-40 °F to 185 °F)
	Operating humidity	5% to 95% (no condensation)
	Storage humidity	5% to 95% (no condensation)
	Power supply	100 to 240 VAC, 50/60 Hz, 2.5 A (Max)
	Power consumption in idle	25 W

## Physical Interface

Front panel:



Back panel:



## Available Model


DS-3E0518P-E/M

## Optional Accessory


SFP Module	Fiber type	Connector	Date Rate	Wavelength	Distance
HK-SFP-1.25G-20-1310	Single fiber, Single-mode	LC	1250 Mbps	Tx1310nm/Rx1550nm	0 to 20 km
HK-SFP-1.25G-20-1550	Single fiber, Single-mode	LC	1250 Mbps	Tx1550nm/Rx1310nm	0 to 20 km
HK-SFP-1.25G-1310-DF-MM	Duplex fiber, Multi-mode	LC	1250 Mbps	Tx1310nm/Rx1310nm	0 to 1 km
HK-SFP-1.25G-20-1310-DF	Duplex fiber, Single-mode	LC	1250 Mbps	Tx1310nm/Rx1310nm	0 to 20 km

### NOTE

HK-SFP-1.25G-20-1310 has to work with HK-SFP-1.25G-20-1550 as a pair.

**Dimension (unit: mm)**

## Typical Application



Distributed by

## HIKVISION

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5888  
www.business@hikvision.com

**Hikvision USA**  
T +1-509-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8593-4233  
sales.au@hikvision.com

**Hikvision India**  
T +91-22-29468900  
sales@pramathikvision.com

**Hikvision Canada**  
T +1-888-200-8900  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-8949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6002  
info.it@hikvision.com

**Hikvision Brazil**  
T +55-11-3318-0850  
letters.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01629-802140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0151172  
sales.africa@hikvision.com

**Hikvision France**  
T +33(0)1-69-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.partikov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vn@hikvision.com

**Hikvision UAE**  
T +971-4-9437090  
sales.me@hikvision.com

**Hikvision Singapore**  
T +65-6884-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-67-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2351-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-659-67-99  
salmu@hikvision.com

**Hikvision Korea**  
T +82-1031-731-8017  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-400-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com