

DS-2CE71D0T-PIRL 2 MP PIR Camera



Key Feature

- 2 MP, 1920 × 1080 resolution
- 2.8 mm, 3.6 mm fixed focal lens
- Smart IR, up to 20 m IR distance
- PIR detection, strobe light alarm
- IP67




Specification

| Camera | |
|--------------------------|--|
| Image Sensor | 2 MP CMOS |
| Signal System | PAL/NTSC |
| Frame Rate | TVI: 1080P@25fps, 1080P@30fps |
| Resolution | 1920 (H) × 1080 (V) |
| Min. illumination | 0.01Lux @ (F1.2, AGC ON), 0 Lux with IR |
| Shutter Time | PAL: 1/25 s to 1/50,000 s NTSC: 1/30 s to 1/50,000 s |
| Lens | 2.8 mm, 3.6 mm fixed focal lens |
| Field of View | 2.8 mm, horizontal FOV:103°, vertical FOV: 56°, diagonal FOV: 122° 3.6 mm, horizontal FOV:82.2°, vertical FOV: 44°, diagonal FOV: 94° |
| Lens Mount | M12 |
| Strobe Light Alarm | Yes |
| Day & Night | ICR |
| WDR (Wide Dynamic Range) | Digital WDR |
| Angle Adjustment | Pan: 0° to 360°, Tilt: 0° to 75°, Rotate: 0° to 360° |
| Menu | |
| White Light | AUTO/OFF |
| Image Mode | STD/HIGH-SAT |
| AGC | Yes |
| Day/Night Mode | Auto/Color/BW (Black and White) |
| White Balance | Auto/Manual |
| AE (Auto Exposure) Mode | DWDR/BLC/HLC/Global |
| Noise Reduction | 2D DNR |
| Language | English |
| Function | Brightness, Sharpness, Mirror, Smart IR |
| Interface | |
| Video Output | 1 HD analog output |
| General | |
| Operating Conditions | -40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensing) |
| Power Supply | 12 VDC ± 25% |
| Power Consumption | Max. 4.5 W |
| Ingress Protection | IP67 |
| Material | Enclosure: Plastic Main body: Metal |
| IR Range | Up to 20 m |
| White Light Range | Up to 20 m |
| PIR Range | Angle: 110°, Range: 11 m |
| Communication | HIKVISION-C |
| Dimensions | Φ 109.8 mm × 89.75 mm (Φ 4.32" × 3.53") |
| Weight | Approx. 327 g (0.72 lb.) |

Order Model

DS-2CE71D0T-PIRL


Dimension




Accessory




DS-1272ZJ-110-TRS
Wall Mount



DS-1275ZJ-SUS
Vertical Pole Mount




DS-1276ZJ-SUS
Corner Mount



DS-1280ZJ-S
Junction Box




DS-1281ZJ-S
Inclined Ceiling Mount



DS-1280ZJ-TR13
Junction Box

Distributed by



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 311051, China
T +86-571-8887-6008
overseasbusiness@hikvision.com

Hikvision USA
T +1-800-855-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8589-4233
sales.au@hikvision.com

Hikvision India
T +91-22-28487000
sales@prianahikvision.com

Hikvision Canada
T +1-800-200-6280
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9040
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6900
info.it@hikvision.com

Hikvision Brazil
T +55-11-3318-0050
latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070-7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7952-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (0)11 0351172
sales.africa@hikvision.com

Hikvision France
T +33 (0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730687
hikla.pienflov@hikvision.ru

Hikvision Vietnam
T +84-674270008
sales.vt@hikvision.com

Hikvision UAE
T +971-4-9432090
sales.me@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-18-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1701
info.hk@hikvision.com

Hikvision Russia
T +7-495-009-67-90
sales.ru@hikvision.com

Hikvision Korea
T +82-031-731-9817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com