

## DS-2CE16D0T-ITF (C) 2 MP Camera



- 2 MP, 1920 × 1080 resolution
- 2.8 mm, 3.6 mm, 6 mm fixed lens
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- Smart IR, up to 30 m IR distance
- IP67






## Specification

Camera	
Image Sensor	2 MP CMOS
Signal System	PAL/NTSC
Resolution	1920 (H) × 1080 (V)
Frame Rate	TVI: 1080P@30fps, 1080P@25fps CVI: 1080P@30fps, 1080P@25fps AHD: 1080P@30fps, 1080P@25fps CVBS: PAL/NTSC
Min. illumination	0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
Lens	2.8 mm, 3.6 mm, 6 mm fixed lens
Field of View	2.8 mm, horizontal FOV: 101°, vertical FOV: 60°, diagonal FOV: 122° 3.6 mm, horizontal FOV: 79.6°, vertical FOV: 43.5°, diagonal FOV: 93.7° 6 mm, horizontal FOV: 51.9°, vertical FOV: 30°, diagonal FOV: 58.8°
Lens Mount	M12
Day & Night	ICR
WDR (Wide Dynamic Range)	Digital WDR
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 90°, Rotation: 0 to 360°
Menu	
Image Mode	STD/HIGH-SAT
AGC	Yes
Day/Night Mode	Auto/Color/BW (Black and White)
White Balance	Auto/Manual
AE (Auto Exposure) Mode	DWDR/BLC/HLC/Global
Noise Reduction	2D DNR
Language	English
Function	Brightness, Sharpness, Smart IR
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
General	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), humidity 90% or less (non-condensing)
Power Supply	12 VDC ± 25%
Power Consumption	Max. 3 W
Protection Level	IP67
Material	Metal
IR Range	Up to 30 m
Communication	HIKVISION-C
Dimensions	57.9 mm × 60.9 mm × 138.8 mm (2.28" × 2.39" × 5.47")
Weight	Approx. 257 g (0.57 lb.)


## Available Model

DS-2CE16D0T-ITF (C)

## Dimension




## Accessory



**DS-1280ZJ-XS**  
**Junction Box**

Distributed by



## HIKVISION

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8907-5998  
overseasbusiness@hikvision.com

### Hikvision USA

T +1-909-885-0400  
sales.usa@hikvision.com

### Hikvision Australia

T +61-2-8589-4211  
salesau@hikvision.com

### Hikvision India

T +91-22-28409800  
sales@prim@hikvision.com

### Hikvision Canada

T +1-866-200-8690  
sales.canada@hikvision.com

### Hikvision Thailand

T +662-271-9949  
sales.thailand@hikvision.com

### Hikvision Europe

T +31-23-6542770  
sales.eu@hikvision.com

### Hikvision Italy

T +39-0438-6902  
info.it@hikvision.com

### Hikvision Brazil

T +55 11 3319-0050  
latam.support@hikvision.com

### Hikvision Turkey

T +90 212521 7070- 7074  
sales.tr@hikvision.com

### Hikvision Malaysia

T +601-2652-2413  
sales.my@hikvision.com

### Hikvision UK & Ireland

T +01526-802140  
sales.uk@hikvision.com

### Hikvision South Africa

Tel: +27 110 0351172  
sales.africa@hikvision.com

### Hikvision France

T +33011-86-330-460  
info.fr@hikvision.com

### Hikvision Kazakhstan

T +7-727-8730667  
nikis.pantlov@hikvision.ru

### Hikvision Vietnam

T +84-074270888  
sales.vt@hikvision.com

### Hikvision UAE

T +971-4-4432080  
sales.ae@hikvision.com

### Hikvision Singapore

T +65-6884-4718  
sg@hikvision.com

### Hikvision Spain

T +34-91-737-16-55  
info.es@hikvision.com

### Hikvision Tashkent

T +99-67-1238-8430  
uzb@hikvision.ru

### Hikvision Hong Kong

T +852-2151-1761  
info.hk@hikvision.com

### Hikvision Russia

T +7-495-659-67-99  
sales.ru@hikvision.com

### Hikvision Korea

T +82-1031-731-8817  
sales.korea@hikvision.com

### Hikvision Poland

T +48-22-460-01-50  
info.pl@hikvision.com

### Hikvision Indonesia

T +62-21-2933759  
Sales.indonesia@hikvision.com

### Hikvision Colombia

sales.colombia@hikvision.com